Combat Descaler

CLEENOL

EST. 1948



Removes built up limescale and removes metal tarnish with ease.

Concentrated formulation, for economy of use.

Fragrance-free formulation, ideal for use in food preparation areas.



2 x 5L | CB269/5

A highly concentrated phosphoric acid descaler, that easily removes limescale deposits from a wide range of surfaces, as well as metal tarnish and rust from ferrous metals. Its fragrance-free formulation allows for it to be safely used in food preparation areas to descale catering equipment. As well as in the leisure industry to clean around the outside of pools, washrooms and changing rooms, removing scale and body fats. Suitable for use on stainless steel and plastics.

Avoid contact with bleach-based products as this may product chlorine gas.

Product Info

Colour: Colourless

Fragrance: Acidic

pH: <1.5

Shelf Life: 24 Months

Directions for use

For professional use only.

For use as a general descaling solution (catering equipment, floors, walls and equipment):

- 1. Always dilute the product before use.
- 2. Dilute the product 50 150 per L water (5-15%) depending on the level of scale present. Always add the product to water and not water to the product.
- 3. Apply by swab, brush, trigger spray or immersion to the surface to be
 - If using to descale kettles or urns, do not boil the solution. Use at room temperature only.
- 4. Leave to sit for a few minutes, agitating stubborn deposits as needed.
- 5. Rinse the cleaned surface with fresh water.



Combat Descaler PA



FST 1048



2 x 5L | CB269/5

Product Info

Colour: Colourless

Fragrance: Acidic

pH: <1.5

Shelf Life: 24 Months

For use in the dairy industry:

- 1. Dilute the product 50-150ml per L water (5-15%) depending on level of scale present.
- 2. Circulate through storage tanks and pipework at 70-80°C after an alkali clean.
- 3. Rinse through with clean water to remove excess product.

For use in the brewing industry:

- 1. Dilute the product 200-500ml per L water (20-50%) depending on level of scale present.
- 2. Circulate through vessels, storage tanks and pipework for 30-45 minutes.
- 3. Rinse through with clean water to remove excess product.

For descaling and cleaning around swimming pools:

- Dilute the product 200ml per L water (20%).
 For severe scale the product can be used undiluted.
- Apply via a mop or machine.
 Avoid contamination of the pool where possible.
- 3. Leave to sit for a few minutes.
- 4. Rinse well with clean water.
- 5. Repeat as needed.

